



RECOMMENDED P.C.B LAYOUT(TOP VIEW)  
TOLERANCES: ±0.10mm

△ SPECIFICATION  
 MATERIAL  
 Insulator: PBT, rated UL94V-0 (standard)  
 Contacts: Brass (Male)  
           Phosphor Bronze (Female)  
 Shell: Steel  
 Rivet,Boardlock: Copper alloy  
 △ CONTACT PLATING  
 Underplate: 50u" Nickel  
 Contact area: 1u"~30u" Selective Gold  
 Solder tails area: 100u" Tin/Lead  
 ELECTRICAL  
 Operation voltage: 250 VAC max.  
 Current rating: 1 Amps max.  
 Contact resistance: 20 mohms max.  
 Insulation resistance: 1000 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 1000 VAC / minute  
 Operating temperature: -55°C TO +125°C

**Allconnectors**  
 www.allconnectors.de  
 Tel.: 0049 711 7006502  
 70754 Hildesheim - Germany  
 Info@allconnectors.de  
 Fax: 0049 711 7006504  
 Kettnerstr. 25

PART NO. UB-PD-2X32		CHECKED BY CY		TOLERANCES ARE		DESCRIPTION: DIN 41612 MALE 64 PIN	
DWG NO. UB-PD-2X32		DRAWING BY		.X .XX ± 0.3 .XXX ± 0.2 AWG		AREA	
FILE NO.		PROJECTION				REVISIONS	
UNIT / mm	SCALE 1:1					HK	DATE