

RECOMMENDED P.C.B LAYOUT(TOP VIEW)
TOLERANCES: ±0.10mm

△ SPECIFICATION

MATERIAL

Insulator: PBT, rated UL94V-0

Contacts: Phosphor Bronze

Rivet, Boardlock: Copper alloy

CONTACT PLATING

Underplate: 50m² Nickel

Contact area: 1m²~30m² Selective gold

Solder tails area: 100m² Tin/Lead

ELECTRICAL

Operation voltage: 250 VAC max.

Current rating: 1 Amps max.

Contact resistance: 20 mohms max.

Insulation resistance: 1000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC / minute

Operating temperature: -55°C TO +125°C

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X ±

.X ± 0.30

.XX ± 0.20


.XXX ±

ANG ±

P PROJECTION



ORDER INFORMATION



DESCRIPTION: DIN 41612 (DUAL ROW) FEMALE 32PIN