

RECOMMENDED P.C.B LAYOUT(TOP VIEW)  
TOLERANCES: ±0.10mm

**△ SPECIFICATION**

**MATERIAL**  
 Insulator: PBT, rated UL94V-0  
 Contacts: Phosphor Bronze  
 Rivet,Boardlock: Copper alloy  
**CONTACT PLATING**  
 Underplate: 50m Nickel  
 Contact area: 1m~30m Selective gold  
 Solder tails area: 100m Tin/Lead  
**ELECTRICAL**  
 Operation voltage: 250 VAC max.  
 Current rating: 1 Amps max.  
 Contact resistance: 20 mohms max.  
 Insulation resistance: 1000 Mohms min @ 500 VDC  
 Dielectric withstanding voltage: 1000 VAC / minute  
 Operating temperature: -55°C TO +125°C


**RoHS Compliant**

**All Connectors**


www.allconnectors.de  
 Tel.: 0049 711 7003503  
 70784 Filberstadt - Germany

info@allconnectors.de  
 Fax: 0049 711 7003504  
 Kettnerstr. 25

DRAWING BY CY		TOLERANCES ARE
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	X ±
DATE		.X ± 0.30
SIZE A4	PJECTION	.XX ± 0.20
		.XXX ±
		ANG ±



**ORDER INFORMATION**



DESCRIPTION: DIN 41612 ( DUAL ROW ) FEMALE 64PIN