

RECOMMENDED P.C.B LAYOUT(TOP VIEW)
TOLERANCES: $\pm 0.10\text{mm}$

△ SPECIFICATION

MATERIAL

Insulator: PBT, rated UL94V-0

Contacts: Brass

Shell: Steel

Rivet, Boardlock: Copper alloy

CONTACT PLATING

Underplate: 50m² Nickel

Contact area: 1m²~30m² Selective gold

Solder tails area: 100m² Tin/Lead

ELECTRICAL

Operation voltage: 250 VAC max.

Current rating: 1 Amps max.

Contact resistance: 20 mohms max.

Insulation resistance: 1000 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC / minute

Operating temperature: -55°C TO +125°C

All connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70734 Filberstadt Germany

info@allconnectors.de
Fax: 0049 711 7009504
Königsplatz 25

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION

TOLERANCES ARE


X \pm

.X ± 0.30

.XX ± 0.20

.XXX \pm

ANG \pm



ORDER INFORMATION



DESCRIPTION: DIN 41612 (DUAL ROW) FEMALE 64PIN