



REV	MODIFICATION	DATE	DRAW	APPROVE
A	New Release	12/31/2003	David	Ivan
B	EC0606062	05/29/2005	Tom	Giordano

Notes :

- Material :**
 Housing : Thermoplastic , UL 94V-0
 Terminal : Copper Alloy
- Finish :**
 Terminal : Selected Gold on Contact Area, Gold Flash on Solder Tails, Both Over 50u" Min. Ni Under-plated Overall
- Order Information :**

X SB0-020 X 2-00T X

T : Lead Free
 N/A : Normal

Amount of Pins
 S : 8 Pins
 ? : ?
 A : 10 Pins

2 : 2u" Min. Gold on Contact Area
 3 : 5u" Min. Gold on Contact Area
 5 : 15u" Min. Gold on Contact Area
 8 : 30u" Min. Gold on Contact Area

Part No.	Dim.	Dim.A	Dim.B
XSBO-02032-00TX	5.0	9.0	
XSBO-02042-00TX	7.5	11.5	
XSBO-02052-00TX	10.0	14.0	
XSBO-02062-00TX	12.5	16.5	
XSBO-02072-00TX	15.0	19.0	
XSBO-02082-00TX	17.5	21.5	
XSBO-02092-00TX	20.0	24.0	
XSBO-020A2-00TX	22.5	26.5	

DIMENSION IN mm [inch]		Allconnectors		Title 2.5mm Pitch Battery Conn. Female Type			
Tolerance unless otherwise specified		www.allconnectors.de Tel: +49 71 23 402540 70754 Filderstadt - Germany		www.allconnectors.de Tel: +49 71 23 402549 Gallersweier, DE		Scale: 4 : 1	
X.	± 0.38	X.'	± 10'	CUSTOMER DRAWING		Dwg No. OSBO-02002-00T0	
X.X	± 0.20	X.X'	± 5'			File No. N/A	
X.XX	± 0.13	X.XX'	± 2'	Approve:	Check:	Draw: Tom	Rev : B
X.XXX	±					05/29/2005	Sheet: 1 / 1

Recommended P.C.B. Layout
 Layout Tolerance = ± 0.05 mm