



No 膠心: Nylon 9T + 30% G.F., UL 94V-0, 黑色
 端子: C5191-H, 鍍厚 = 0.2±0.01mm
 2. 電鍍:
 端子: 對接區: 選鍍金
 焊接區: 1u"Min. 金
 鍍底: 50u"Min.

BCC25-SV65R2P-xx-LF
 LEADFREE

RoHS Compliant

Dimension Information:

Part No.	Dim.	Dim.A	Dim.B	Dim.C	Dim.D
BCC25-SV65R2P-04	17.7	13.7	10.00	9.15	
BCC25-SV65R2P-05	20.2	16.2	12.50	11.65	
BCC25-SV65R2P-06	22.7	18.7	15.00	14.15	
BCC25-SV65R2P-07	25.2	21.2	17.50	16.65	
BCC25-SV65R2P-08	27.7	23.7	20.00	19.15	
BCC25-SV65R2P-09	30.2	26.2	22.50	21.65	
* BCC25-SV65R2P-10	32.7	28.7	25.00	24.15	

* 已生產之Pin數

Allconnectors
 www.allconnectors.de
 Tel: 0049 711 7094103
 40784 Hildesheim Germany
 info@allconnectors.de
 Fax: 0049 711 7094104
 Kottbörnerstr. 25

PART NO. BCC25-SV65R2P-xx

DWG NO. BCC25-SV65R2P-xx

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

Housing for 2.5mm Pitch
 Battery Conn. Female Type

FILE NO.

DRAWING BY

.X±0.2
.XX±0.1
.XXX±
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION