

- NOTES:
- 1. MATERIAL:
 - 1.1 HOUSING: THERMOPLASTIC, HIGH TEMP., UL94V-0; COLOR:NATURAL.
 - 1.2 CONTACT: COPPER ALLOY
 - 2. FINISH:
 - 1:GOLD FLASH PLATING(1~3u")
 - N:100~200u" MATT TIN PLATING
 - 50~100u" NICKEL UNDERPLATING OVERALL.
 - 3. REFLOW SOLDER CAPABLE TO 260°C

CKT	DimA	DimB	DimC	DimD	DimE
40	11.4	14.7	17.0	18.6	16.2
60	17.4	20.7	23.0	24.6	22.2
80	23.4	26.7	29.0	30.6	28.2
90	26.4	29.7	32.0	33.6	31.2
100	29.4	32.7	35.0	36.6	34.2
120	35.4	38.7	41.0	42.6	40.2
140	41.4	44.7	47.0	48.6	46.2
160	47.4	50.7	53.0	54.6	52.2

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

RoHS Compliant


DRAWING BY CY
CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4 PROJECTION

TOLERANCES ARE
X ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

FX8-P09PC-xxx-LF

SERIES PLUG POST CAP LEADFREE

040~160WAY

UNMATED HIGH 0.9mm

DESCRIPTION: 0.6mm BTB PLUG SMT S/T D/R TYPE