



NOTES:

- Specifications  
 Current Rating: 0.5Amp  
 Insulation Resistance: 1000MΩ Min.  
 Dielectric Withstanding: 300VAC  
 Contact Resistance: 20mΩ Max.  
 Operating Temperature: -40°C to +105°C
- Materials  
 Contact Material: BRASS  
 Insulator Material: PA9T UL94V-0 本色
- All materials must be GP materials

Ordering Information

BFESH1 - XX XX 01 X

No. of Pins Per Row: 05-30

Standard Plating:  
 01=Gold Flash  
 02=Gold 3U"  
 11=Tin  
 XX=Select Plating

Packing:  
 T=Tube  
 TP=Tape Reel

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN DATE	 www.allconnectors.eu   info@allconnectors.eu Tel. +49 (0)711 / 358 110 20   Fax +49 (0)711 / 358 110 25	
X. ±	X°. ±5'	Andy2008.08.12		
.X ±0.38	.X' ±2'	CHECK DATE	FILE NAME (品名)	0.8mm Bord To Bord MALE
.XX ±0.25	.XX' ±1'	APPRO. DATE	PART NO (料号)	BFESH1-XXXX01X
.XXX ±0.13	.XXX' ±0.5'		DRAWING NO.(图号)	BFESH-01
UNIT:mm	SCALE 1:1			REV.A0
A4	SHEET: 1 of 1			