


- Current Rating: 1 Amps
- Insulator Resistance: 5000 Megohms min
- Dielectric Withstanding: AC 500 V
- Operating Temperature: - 40° ~ +85° C
- Max Processing Temp: 230°C for 60 seconds
- Max Processing Temp: 260° C for 10 seconds
- Contact Material: Copper Alloy
- Insulator Material: Polyester, UL 94V-0
Standard: Nylon-6T

Finish: Gold Plated
Standard: Gold Flash all over

All Connectors
www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettenerstr. 25

RoHS Compliant		TOLERANCES ARE	
DRAWING BY CY		X ±	
CHECKED BY GENIUS		.X ±	
UNIT/ mm	SCALE 1 : 1	.XX ±	
DATE		.XXX ±	
SIZE A4	PJECTION	ANG ±	



ORDER INFORMATION

PAB-WX-2Xxx-LF

```

    SERIES --- PAB-WX-2Xxx-LF --- LEADFREE
                    |
                    |--- 2X05:10WAY
                    |--- 2X50:100WAY
                    |
                    |--- 90°SMT
                    |--- NON POST
  
```

DESCRIPTION: