


剖面 A-A



■ Specifications (规格):

- Voltage rating (额定电压): 250V AC / DC
- Current rating (额定电流): 3A AC / DC
- Withstanding voltage (耐压值): 800V AC/minute
- Temperature range (工作温度): -25° C~+85° C
- Insulation resistance (绝缘电阻):  $\geq 1000M\Omega$
- Contact resistance (接触电阻):  $\leq 10m\Omega$
- After environmental testing (环境测试后):  $\leq 20m\Omega$
- Important Dimensions: with '\*' mark (带\*标志, 表示重点尺寸)
- Key Dimensions: with '#' mark (带#标志, 表示关键尺寸)

■ Plastic Material (塑胶材质): PA66+30%GF UL94V-0,



- Color (颜色): Creamy White (米白色),
- Contacts Material (端子材质): Brass.
- Finish (端子电镀): Tin-plated (镀锡),

A2019 HI - NP - N0 CW T  
① ②③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-Housing
- ③ Housing Type: I-Prick Housing.
- ④ Pin No.: 02-02PIN~15-15PIN.
- ⑤ Material: N0-PA66,UL94V-0.
- ⑥ Color: CW-Creamy White.
- ⑦ Plating Specification: T-Tin Plated

Ordering Information & Dimensions

Poles	Dimensions(mm)	
	A	B
02	2.00	6.00
03	4.00	8.00
04	6.00	10.00
05	8.00	12.00
06	10.00	14.00
07	12.00	16.00
08	14.00	18.00
09	16.00	20.00
10	18.00	22.00
11	20.00	24.00
12	22.00	26.00
13	24.00	28.00
14	26.00	30.00
15	28.00	32.00

						 www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany info@allconnectors.de Fax: 0049 711 7009504 Keltnerstr. 25	料号 PART NO A2019HI-NP-N0CWT							
							品名 TITLE 2.00mm Pitch 90° Single Row Wafer							
日期 DATE	旧版次 OLD REV	新版次 NEW REV	变更内容 DESCRIPTION	审核 CHK	核准 APPD	角法 PROJECT 	核准 APPD Rodney	审核 CHK 兰雄	绘图 DR 唐文舜	日期 DATA 2018/12/03	单位 UNIT mm	比例 SCALE 1/1	图号 NUMBER 8802	版次 REV A