





2.00mm PITCH BOX HEADER, SHROUDED TERMINAL STRIP ELEVATED, SMT, DOUBLE ROW, ROHS COMPLIANT



Material Information:

Terminal: Brass
 Insulator: PA6T+30%G.F (UL94V-0)
 Plating: Au or Sn plated over 50 U" Ni
 All materials compliant with ROHS

Technical Specifications:

Current Rating: 1.5A
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000mΩ Min.
 Dielectric Voltage: 500V AC/minute
 Operation Temperature: -40° C to +105° C

Ordering Information

BBM77 - XX XX XX B1 X
 ① ② ③

- ① No. of Contacts: 06 To 64
- ② Plating Option:
 01: Gold Flash Over All
 05: 5U' Gold plated Over All
 10: 10U' Gold Plated Over All
 0S: Tin Plated Over All
- ③ Packing Option:
 A: Plastic Tray B: PE Bag
 C: Tube



www.allconnectors.de
 Tel: 0049 711 7099603
 70754 Filderstadt - Germany

Info@allconnectors.de
 Fax: 0049 711 7099504
 kettemer@allconnectors.de

绘图 (DRAWN) 孙高田
 审核 (CHECKED) 刘思晴
 核准 (APPROVE)

投影 (PROJECT) 孙高田
 单位 (UNIT) MM
 比例 (SCALE) 1:1
 版本 (EDITION) A
 日期 (DATE) 2013/12/14

公差 (TOLERANCE) 0.0 ± 0.30
 0.00 ± 0.20

料号 (PART NO) BBM77-XXXXXXB1X
 品名 (NAME) 2.0筒牛 加塑 立贴