



P.C.Board Layout

HAL-D-xxx-LF
LEADFREE
006:6PIN
068:68PIN
RoHS Compliant

Circuits	Dimension		
	A	B	C
6	2.54	18.31	8.46
10	5.08	20.85	11.00
12	6.35	22.12	12.27
14	7.62	23.39	13.54
16	8.89	24.66	14.81
20	11.43	27.20	17.35
26	15.24	31.01	21.16
30	17.78	33.55	23.70
34	20.32	36.09	26.24
40	24.13	39.90	30.05
44	26.67	42.44	32.59
50	30.48	46.25	36.40
60	36.83	52.60	42.75
64	39.37	55.14	45.29
66	40.64	56.41	46.56
68	41.91	57.68	47.83

Contact:
Contact:Brass.
Insulator:LCP.
Finish:Gold flash plated over nickel.

Allconnectors
www.allconnectors.de
Tcl.: 0049 711 7009503
20764 Bildebacht Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kottentorstr. 25

PART NO. HAL-D-xxx		CHECKED BY CY		TOLERANCES ARE .X±0.2 .XX±0.1 .XXX± AWG	DESCRIP TION: 1.27-1.27 Pitch Shrouded Header Stright Type			
DWG NO. HAL-D-xxx		DRAWING BY			AREA	REVISIONS	HK	DATE
FILE NO.		PROJECTION						
UNIT / mm	SCALE 1:1							