



NOTES:

1. MATERIAL:
 - 1-1 Housing : Engineering plastic , LCP with G.F reinforced , black per UL 94V-0 rate.
 - 1-2 Terminal : Phosphor Bronze , per JIS 5210 , 0.2t
 - 1-3 Metal cover : Stainless steel sheet SUS304 0.2t.
2. PLATING:
 - Contact area: 0.254 μ m (10 μ " minimum) or 0.762 μ m (30 μ ") gold plating
 - Solder zone: 2.54 μ m (100 μ ") matte Tin 1.27 μ m (50 μ ") min. Nickel underplating over all.
3. RoHS compliant products.
4. OPERATING TEMPERATURE: -40°C~+85°C

1. CONTACT TYPE: Male
2. CONTACT NUMBER: 24
3. SHELL MATERIAL: Stainless steel 8.35H
4. SOLDER TAILS AREA PLATING: TIN

RoHS Compliant		TOLERANCES ARE	
		X \pm .X \pm 0.30 .XX \pm 0.20 .XXX \pm ANG \pm	
		DRAWING BY CY CHECKED BY GENIUS	
www.allconnectors.de Tel.: 0049 711 7009503 70794 Filderstadt - Germany	info@allconnectors.de Fax: 0049 711 7009504 Kettenerstr. 25	UNIT/ mm SCALE 1 : 1 DATE SIZE A4	PPROJECTION



ORDER INFORMATION			
CFA-PW30CE221-24-HF			
SERIES	MALE	90°SMT	24WAY HALOGEN FREE
POST TO POST 30.0mm	EAR	STANDOFF 2.0mm	NORMAL
C TYPE		TYPE 2	
DESCRIPTION: CFAST HOST CONNECTOR MANU TYPE II,8.35H			