

SPECIFICATION

MATERIAL

Insulator: Thermail Plastic UL 94V-0
 Contacts: Copper Alloy
CONTACT PLATING
 Underplate: 50u" Nickel
 Contact area: 1u"~30u" Selective gold

ELECTRICAL

Operation voltage: 250 VAC max.
 Current rating: 3 Amps max.
 Contact resistance: 15 mohms max.
 Insulation resistance: 3000 Mohms min @ 500 VDC
 Dielectric withstanding voltage: 1000 VAC / minute
 Operating temperature: -55°C TO +105°C


POSITION	A	B	C	D
DFM-P-09	16.92	25.00	30.8	22.4
DFM-P-15	25.25	33.30	39.2	30.8
DFM-P-25	38.96	47.10	53.1	44.5
DFM-P-37	55.42	63.50	69.4	61.4

RoHS Compliant

All Connectors

www.allconnectors.de info@allconnectors.de
 Tel.: 0049 711 7009503 Fax: 0049 711 7009504
 70794 Filderstadt - Germany Kettnerstr. 25

DRAWING BY CY		TOLERANCES ARE
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	.X ± 0.30
DATE		.XX ± 0.20
SIZE A4	PPOJECTION	.XXX ±
		ANG ± 5°



ORDER INFORMATION

DFM-P-xx-LF
 SERIES | LEADFREE
 09~37WAY
 MALE

DESCRIPTION: D-SUB IDC FOR FLAT RIBBON CABLE