

PCB LAYOUT

ELECTRICAL CHARACTERISTICS

Dielectric withstanding Voltage: 1000VAC for
one minute at sea level.

Insulation Resistance: >1000MΩ

Operating Temperature: -55°C to +105°C

MATERIAL

Insulator: PBT.

Power Contact: Copper Alloy.

Shell: SPCC.

PART NO.	Current Rating	Dimension	Dimension
		Ø A	ØB
03	40 AMPS	Ø3.75	Ø4.20
02	20 AMPS	Ø2.8	Ø3.25
01	10 AMPS	Ø1.7	Ø2.20

DWD-Sxx-07W2-LF

40:40AMPS
20:20AMPS
10:10AMPS

LEADFREE

RoHS Compliant

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70721 Filberstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kellnerstr. 25

PART NO. DWD-Sxx-07W2

DWG NO. DWD-Sxx-07W2

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ±
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE