



MATERIALS AND FINISH
 SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED
 BACK SHELL TIN FINISHED
 DIMPLES ON PLUG ONLY
 INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,
 UL 94V-0 RATED, BLACK COLOR
 SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

ELECTRICAL CHARACTERISTICS
 CONTACT CURRENT RATING : 5.0 AMPS
 CONTACT RESISTANCE : 10 mΩ MAX.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.
 INSULATION RESISTANCE : 5GΩ MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

DWS-S-07W2-LF
 LEADFREE
 RoHS Compliant

Allconnectors
 www.allconnectors.de
 Tel: 0049 711 7085503
 70764 Tübingen - Germany
 info@allconnectors.de
 Fax: 0049 711 709504
 Kellernstraße 25

PART NO. DWS-S-07W2		CHECKED BY CY	TOLERANCES ARE .X±0.2 .XX±0.1 .XXX± AWG	DESCRIPTION:			
DWG NO. DWS-S-07W2							
FILE NO.		PROJECTION	AREA	REVISIONS	HK	DATE	
UNIT / mm	SCALE 1:1						