



**MATERIALS AND FINISH**

SHELL : STEEL MATERIAL, FRONT SHELL TIN FINISHED  
 BACK SHELL TIN FINISHED  
 DIMPLES ON PLUG ONLY

INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED,  
 UL 94V-0 RATED, BLACK COLOR

SIGNAL CONTACT : COPPER ALLOY, FULL GOLD FLASH

**ELECTRICAL CHARACTERISTICS**

SIGNAL CONTACT CURRENT RATING : 5.0 AMPS

SIGNAL CONTACT RESISTANCE : 2.7 mΩ MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC FOR 1 MINUTE

INSULATION RESISTANCE : 5GΩ MIN.

TEMPERATURE RATING : -55°C ~ +125°C

DWS-S-17W2-LF  
 LEADFREE

RoHS Compliant

**Allconnectors**

www.allconnectors.de  
 TEL: 0399 711 4036/3  
 41249 Hildersbach - Germany

info@allconnectors.de  
 FAX: 0399 711 2005/04  
 Kettnerstr. 21

PART NO. DWS-S-17W2

DWG NO. DWS-S-17W2

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ± 0.20

.X ± 0.10

.XX ± 0.05

.XXX ± 0.03

ANG

DESCRIPTION:			
AREA	REVISIONS		DATE