



PCB LAYOUT

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
DIMPLES ON PLUG ONLY

CONNECTOR INSULATOR : PBT THERMOPLASTIC,
30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
COAXIAL INSULATOR : TEFLON UL 94V-0 WHITE COLOR
SIGNAL CONTACT MATERIAL: BRASS, FULL GOLD FLASH
COAXIAL CONTACT MATERIAL: BRASS, 15u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING : 3.0 AMPS
SIGNAL CONTACT RESISTANCE : 10 MILLIOHMS MAX.
DIELECTRIC WITHSTANDING VOLTAGE :
1000 V AC FOR 1 MINUTE
INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
TEMPERATURE RATING : -55°C ~ +125°C
COAXIAL CONTACT IMPEDANCE: 75 OHMS

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70734 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettelerstr. 25

PART NO. DXS-P75-11W1

DWG NO. DXS-P75-11W1

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X±0.2
.XX±
.XXX±
AWG

DESCRIPTION:

D-SUB CONNECTOR
(Coaxial Contact Solder Type)

AREA

REVISIONS

HK

DATE