

**Note:**

**1.Material:**

- 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
- 1.2 Contact: Copper alloy,t=0.20mm
- 1.3 Shell: Spcc,t=0.30mm

**2.Specification:**

- 2.1 Current rating: 1 A Max.
- 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
- 2.3 Contact resistance: 30 mΩ Max.
- 2.4 Insulation resistance: 1000 MW Min.
- 2.5 Total mating force: 7.0 Kgf Max.
- 2.6 Total unmating force: 1.5 Kgf Min.
- 2.7 Temperature range: -55°C~85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I± 0.10
DC-P-09	30.81	24.99	16.92	8.36	17.7		12.55	2.77	2.84
DC-P-15	39.25	33.32	25.25	8.36	17.7		12.55	2.77	2.84
DC-P-25	53.04	47.04	38.96	8.36	17.7		12.55	2.77	2.84
DC-P-37	69.50	63.50	55.42	8.36	17.7		12.55	2.77	2.84

**All Connectors**  
 www.allconnectors.de  
 Tel.: 0049 711 7009503  
 70794 Filderstadt - Germany

**RoHS Compliant**

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT/mm SCALE 1:1  
 DATE  
 SIZE A4


TOLERANCES ARE

X ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PROJECTION



**ORDER INFORMATION**



**DESCRIPTION: D-SUB CRIMP (M)**