



RECOMMENDED P.C.B. LAYOUT

### SPECIFICATIONS

#### ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 3 Amperes.  
 Dielectric Withstanding Voltage: AC 1000/60sec.r.m.s.  
 Insulation Resistance: 500 MΩohms Minimum at DC 500V.  
 Contact Resistance: 25 Milliohms Maximum.  
 Operating Temperature: -55°C to +105°C.

#### MECHANICAL CHARACTERISTICS:

Contact Insertion Force: 341 g. Maximum.  
 Contact Separation Force: 21 g. Minimum.  
 Grounding Screw Torque: 3 Kg. Minimum.

#### MATERIALS:

Contacts: Brass.  
 Insulator: PBT UL 94V-0 Rated.  
 Shell: Cold Roller Steel.  
 Grounding Screw Torque: Brass

#### FINISHES:

Contact: Gold Flash.  
 Shell: Nickel Plated.

DCD11-PSZJ-09-LF

LEADFREE

RoHS Compliant

**Allconnectors**

www.allconnectors.de  
 T. +49 711 7005503  
 70754 Filzschacht (Germany)

info@allconnectors.de  
 Fax: +49 711 7005504  
 kett@connectors.de

PART NO. DCD11-PSZJ-09

DWG NO. DCD11-PSZJ-09

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
 .XX ± 0.1  
 .XXX ±  
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE