

- Note:**
- 1. Material:
 - 1.1 Insulator: High temperature thermoplastic with g.f, UL94v-0
 - 1.2 Contact: Copper alloy, t=0.20mm
 - 1.3 Shell: Spcc, t=0.30mm
 - 2. Specification:
 - 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 mΩ Max.
 - 2.4 Insulation resistance: 1000 MW Min.
 - 2.5 Total mating force: 7.0 Kgf Max.
 - 2.6 Total unmating force: 1.5 Kgf Min.
 - 2.7 Temperature range: -55°C~85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I±0.10
DD-PGZJ-09	30.81	24.99	16.92	8.38	16.9		12.55	2.77	2.84
DD-PGZJ-15	39.25	33.32	25.25	8.38	16.9		12.55	2.77	2.84
DD-PGZJ-19	44.80	38.86	30.6	8.38	16.9		12.55	2.77	2.84
DD-PGZJ-23	50.30	44.3	35.9	8.38	16.9		12.55	2.77	2.84
DD-PGZJ-25	53.04	47.04	38.96	8.38	16.9		12.55	2.77	2.84
DD-PGZJ-37	69.50	63.50	55.42	8.38	16.9		12.55	2.77	2.84

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

RoHS Compliant

TOLERANCES ARE


X ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

DRAWING BY CY
CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PROJECTION



ORDER INFORMATION

DD-PGZJ-xx-LF

SERIES MALE CLIP FULL GOLD JACKSCREW LEADFREE 09~37WAY

DESCRIPTION: D-SUB P.C.B MALE (鯽魚叉鎖螺絲)