



SPECIFICATION

MATERIAL

Insulator: Thermal Plastic UL94V-0
 Contacts: Copper Alloy
 Shell: Steel
 Rivet, Boardlock: Copper Alloy

CONTACT PLATING

Underplate: 50u" Nickel
 Contact Area: 1u"~30u" Selective Gold
 Solder Tails Area: 100u" Tin/Lead(Brighten Tin) or
 100u" Tin/Lead Free(Brighten Tin/Matte Tin)

ELECTRICAL

Operation Voltage: 250 VAC max.
 Current Rating: 3 Amps max.
 Contact Resistance: 15 mohms max.
 Insulation Resistance: 3000 Mohms min @ 500 VDC
 Dielectric Withstanding Voltage: 1000 VAC / minute
 Operating Temperature: -55°C TO +105°C

DDF-PG-xx-LF
 LEADFREE

RoHS Compliant

POSITION	A	B	C	D
9M	16.92	25.00	30.8	19.2
15M	25.25	33.30	39.2	27.7
25M	38.96	47.10	53.1	41.1
37M	55.42	63.50	69.4	57.3

All Connectors
 www.allconnectors.de
 TEL: 0049 711 7099503
 70734 Hildersstadt Germany
 info@allconnectors.de
 FAX: 0049 711 7005504
 Kottbusstr. 22

PART NO. DDF-PG-xx		CHECKED BY CY	TOLERANCES ARE X±0.2 .XX± .XXX± AWG	DESCRIPTION:			
DWG NO. DDF-PG-xx							
FILE NO.		PROJECTION		AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1						