



RECOMMENDED P.C.B LAYOUT (TOP VIEW)
TOLERANCES: $\pm 0.05\text{mm}$

CONTACT LENGTH
DIM. FOR "Y":

13	13.0mm
09	9.5mm

POSITION	A	B	C	D
9F	16.30	25.00	30.8	19.2
15F	24.60	33.30	39.2	27.7
19F	30.00	38.86	44.8	32.8
23F	35.30	44.30	50.3	38.3
25F	38.30	47.10	53.1	41.1
37F	54.80	63.50	69.4	57.3

- ▲ SPECIFICATION
- MATERIAL
 - Insulator: Thermal Plastic UL94V-0
 - Contacts: Copper Alloy
 - Shell: Steel
- ▲ Rivet, Boardlock: Copper Alloy
- CONTACT PLATING
 - Underplate: 50u" Nickel
 - Contact Area: 5u"~30u" Selective Gold
- ELECTRICAL
 - Operation Voltage: 250 VAC Max.
 - Current Rating: 3 Amps Max.
 - Contact Resistance: 15 mohms Max.
 - Insulation Resistance: 3000 Mohms Min @ 500 VDC
 - Dielectric Withstanding Voltage: 1000 VAC / Minute
 - Operating Temperature: -55°C To +105°C

DDL-Sxx-xx-LF
 └──┬──┘ LEADFREE
 09:9.5mm
 13:13.0mm

RoHS Compliant

Allconnectors

www.allconnectors.com
 Tel.: 0049 7141 909403
 71736 Ulm/Neu-Ulm - Germany

Info: info@allconnectors.com
 Fax: 0049 7141 909401
 BERNHARDT 21

PART NO. DDL-Sxx-xx

DWG NO. DDL-Sxx-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

X ± 0.2
 XX ± 0.1
 XXX \pm
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE