



Recomended PCB Layout

Specifications

Contact Resistance: $\approx 30m$ max. at DC
 100mA
 Insulator Resistance: 1000M min. at DC
 500V
 Current Rating: 5 AMP
 Dielectric Withstanding
 Voltage: AC 1000V For 1 minute
 Operating Temperature: $-55^{\circ}C \sim +105^{\circ}C$
 Contact: Brass
 Housing: PBT & 30% Glass Fiber (UL
 94V-0)

Dimension

Positon	A	B	C
9	16.92	24.99	30.81
15	25.50	33.32	39.14
25	38.96	47.04	53.04
37	55.42	63.50	69.32

RoHS Compliant

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70754 Filderstadt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kettnerstr. 25

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

TOLERANCES ARE

X \pm
 .X \pm 0.10
 .XX \pm 0.05
 .XXX \pm
 ANG \pm



ORDER INFORMATION

DDM-P-xx-LF
 SERIES | T LEADFREE
 09-37WAY
 MALE

DESCRIPTION: D-SUB DIP STRAIGHT TYPE W/O METAL REAT SHELL