



MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0),BLACK.
 CONTACT MATERIAL : BRASS.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL FINISH : STEEL NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 5 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15mΩ MAX. 10 SEC.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

SHELL SIZE	Dim A ± 0.20	Dim B ± 0.25	Dim C ± 0.38	Dim D
09 pin	16.92	24.99	30.80	11.08
15 pin	25.25	33.32	39.10	19.39
25 pin	38.96	47.04	53.00	33.24
37 pin	55.42	63.50	69.32	49.86

RoHS Compliant

All Connectors

www.allconnectors.de
 Tel.: 0049 711 7009503
 70794 Filzstätt - Germany

info@allconnectors.de
 Fax: 0049 711 7009504
 Kellernstr. 25

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

TOLERANCES ARE

X ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

DR-PSJ-xx-LF
 SERIES | LEADFREE
 | | 09~37 WAY
 | | JACKSCRW
 | | SEMI GOLD
 | | MALE

DESCRIPTION: D-SUB CONN. RIGHT ANGLE , MALE FOOTPRINT : 8.08mm