

NOTES:

1.MATERIAL

- 1.1 Insulator: PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact: Brass
- 1.3 Contact Plating: Gold Plated
- 1.4 Shell: Gold (5U) Plated

2.SPECIFICATION

- 2.1 Current Rate: 5 Amps
- 2.2 Insulator Resistance: 1000M ΩMin. at 500V DC
- 2.3 Dielectric Strength: 1000V Per minute
- 2.4 Operation Temperature: -55°C to +105°C

No. of Contacts	Dim. A	Dim. B	Dim. C	Dim. D
DR-PxNJ-09	16.92	24.99	30.81	11.08
DR-PxNJ-15	25.25	33.32	39.14	19.39
DR-PxNJ-25	38.96	47.04	53.04	33.24
DR-PxNJ-37	55.42	63.50	69.32	49.86

All Connectors

www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettenerstr. 25

RoHS Compliant

TOLERANCES ARE


DRAWING BY CY
CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4 PROJECTION

X ±
X ± 0.50
.XX ± 0.30
.XXX ±
ANG ±



ORDER INFORMATION

DR-PxNJ-xx-LF

SERIES: DR-PxNJ-xx-LF

MALE: DR-PxNJ-xx-LF

09~37WAY: DR-PxNJ-xx-LF

LEADFREE: DR-PxNJ-xx-LF

NUT+JACKSCRW: DR-PxNJ-xx-LF

G: FULL GOLD
S: SEMI GOLD

DESCRIPTION: DR 公叉鉚鎖黑 8.1 RoHS