



P.C.B. LAYOUT

NOTES:

1.MATERIAL

- 1.1 Insulator:PBT+30%Glass Fiber (UL94V-0)
- 1.2 Contact: Brass
- 1.3 Contact Plated:Gold or Tin Plated
- 1.4 Shell:Steel,Nickel Plated
- 1.5 Screw:Brass, Nickel Plated

2.SPECIFICATION

- 2.1 Current Rate:5 Amps
- 2.2 Insulator Resistance:5000MΩ Min. at 500V DC
- 2.3 Dielectric Strength:1000V Per minute
- 2.4 Operation Temperature:-55C to+105C

DR50-PN-09-LF
LEADFREE

RoHS Compliant

Allconnectors

www.allconnectors.de
Tel.: 0049 711 7009503
70754 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

PART NO. DR50-PN-09

DWG NO. DR50-PN-09

CHECKED BY CY

TOLERANCES ARE

DESCRIPTION:

DR9公卿附全金黑 5.08 無毒

FILE NO.

DRAWING BY

.X±0.2
.XX±
.XXX±
AWG

AREA

REVISIONS

HK

DATE

UNIT / mm

SCALE 1:1

PROJECTION

