



RECOMMENDED P.C.B. LAYOUT

MATERIALS:

Contacts: Brass.

Insulator: PBT POLYESTER, UL 94V-0 Rated.

Shell: Cold Roller Steel.

FINISHES:

Contact: Gold Flash.

Shell: Nickel Plated.

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 5 Amperes.

Dielectric Withstanding Voltage: AC 1000V/60sec. r.m.s.

Insulation Resistance: 5000 Megohms Minimum. at DC 500.

Contact Resistance: 25 Milliohms Maximum.

Operating Temperature: -55°C to +105°C.

MECHANICAL CHARACTERISTICS:

Contact Insertion Force: 341 g. Maximum.

Contact Separation Force: 21 g. Minimum.

RoHS Compliant

All Connectors

www.allconnectors.de
Tel.: 07049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 07049 711 7009504
Kettnerstr. 25

DRAWING BY CY		TOLERANCES ARE
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	X ±
DATE		.X ±
SIZE A4	P PROJECTION	.XX ±
		.XXX ±
		ANG ±



ORDER INFORMATION

DRB1-FNJ-2500-LF		
SERIES	LEADFREE	
	25WAY	
	JACKSCRW	
	NUT	
	FEMALE	

DESCRIPTION: D-SUB 25 FEMALE HIGH RAISE