

**MATERIAL:**

INSULATOR : PBT, UL 94V-0.  $\Delta$   
 CONTACT : COPPER ALLOY.  
 CONTACT FINISH : GOLD OVER NICKEL.  
 SHELL : STEEL.  
 BOARDLOCK : BRASS, TIN PLATED.  
 RIVETED INSERT : BRASS, NICKEL PLATED.

**SPECIFICATION:**

CURRENT RATING : 5 AMP  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC FOR 1 MINUTE.  
 INSULATION RESISTANCE : 1000MQ MIN. AT 500V DC.  
 CONTACT RESISTANCE : 15mΩ MAX.  
 OPERATING TEMPERATURE : -55°C ~ +105°C.

POSITION	A ± 0.20	B ± 0.20	C ± 0.38	D
09 PIN	16.90	25.00	30.80	11.08
15 PIN	25.25	33.30	39.20	19.39
25 PIN	38.95	47.05	53.05	33.24
37 PIN	55.40	63.50	69.40	49.86

RoHS Compliant


**All Connectors**

www.allconnectors.de info@allconnectors.de  
 Tel.: 0049 711 7009503 Fax: 0049 711 7009504  
 70791 Hilderstadt - Germany Kettnerstr. 25

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

TOLERANCES ARE

X ±  
 .X ± 0.25  
 .XX ± 0.15  
 .XXX ± 0.05  
 ANG ±



ORDER INFORMATION

DRL-PGN-xx-LF  
 SERIES | | | LEADFREE  
 | | | 09-37WAY  
 | | | NUT  
 | | | FULL GOLD  
 | | | MALE

DESCRIPTION: D-SUB CONN RIGHT ANGLE , MALE FOOTPRINT : 14.84mm