



MATERIAL & FINISH

SHELL : STEEL NICKEL OR TIN PLATED
 PIN CONTACT: BRASS GOLD PLATED OVER NICKEL
 INSULATOR : PBT & GLASS-FIBRE REINFORCED
 NUMBER OF CONTACT : 09P, 15P, 25P, 37P
 CURRENT RATING : 7.5 amp.
 DIELECTRIC STRENGTH : 1000V FOR ONE MINUTE
 INSULATOR RESISTANCE : TEMPERATURE : - 55°C~+105°C

ITEM No.	A	B	C	D	E	F	G	H
09	16.92	24.99	30.81	19.23	1.00	10.80	2.70	5.84
15	25.25	33.32	39.14	27.56	1.00	10.80	2.70	5.84
25	38.96	47.04	53.04	41.30	1.00	10.80	2.70	5.84
37	55.42	63.50	69.32	57.71	1.00	10.80	2.70	5.84
50	52.86	61.11	66.92	55.30	1.00	10.80	2.70	5.84

RoHS Compliant

All Connectors

www.allconnectors.de
 info@allconnectors.de
 Tel.: 0049 (0) 71 3039413
 Fax: 0049 (0) 71 3039414
 70794 Fildefeld Germany
 R: 00000001.25

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PROJECTION

TOLERANCES ARE

X ±
 X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

DSM-Pxxx-xx-LF
 SERIES | LEADFREE
 | 09~50WAY
 | BLANK: GOLD PLATED
 | G03: GOLD PLATED 03u"
 MALE :

DESCRIPTION: