



(DB15M/HD15F ADAPTOR)

PIN OUT: 15Male 15Female

1, shell	-----	4,5,6,7,8,10,11 shell
2	-----	1
4, shell	-----	4,5,6,7,8,10,11 shell
5	-----	2
6, shell	-----	4,5,6,7,8,10,11 shell
7	-----	DIODE
9	-----	3
12	-----	14
13	-----	4,5,6,7,8,10,11 shell
15	-----	13

Label: orange color with white character
 One side: VGA ADAPTOR HD15/DB15
 The other side: VGA ADAPTOR HD15/DB15
 SPECIFICATION
 INSULATOR: PBT Glass fibre reinforced UL 94 V0
 CONTACT: Brass
 CONTACT PLATING: Gold plated over nickel
 SHELL: Tin plated shell
 CURRENT RATING: 3 AMP
 DIELECTRIC STRENGTH: 500V AC for one minute
 INSULATOR RESISTANCE: 500M Ω min at 500V DC
 TEMPERATURE: -25 $^{\circ}$ C—+105 $^{\circ}$ C

DBHD-ES-1515-LF
LEADFREE

RoHS Compliant

Allconnectors

www.allconnectors.de
 info@allconnectors.de
 Tel.: 0749 711 7005509
 Fax: 0749 711 7005504
 RUDOLF HILDEBRANDT - Germany
 Kettnerstr. 20

PART NO. DBHD-ES-1515

DWG NO. DBHD-ES-1515

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X±0.2
 .XX±
 .XXX±
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE