



DGC 15 M/F GENDER CHANGER  
PIN OUT: 15Male 15Female

1	-----	1
2	-----	2
14	-----	14
15	-----	15
G	-----	G

Label: yellow color with black character  
 One side: MINI GENDER CHANGER  
 The other side: U.S.A. PATENT 5199906 GENERAL CHANGES  
**SPECIFICATION**  
 INSULATOR: PBT Glass fibre reinforced UL 94 V0  
 CONTACT: Brass  
 CONTACT PLATING: Gold plated over nickel  
 SHELL: Tin plated shell  
 CURRENT RATING: 3 AMP  
 DIELECTRIC STRENGTH: 1000V AC for one minute  
 INSULATOR RESISTANCE: 1000MΩ min at 500V DC  
 TEMPERATURE: -55°C — +105°C

DBX2-ES-1515-LF  
LEADFREE

RoHS Compliant

**All Connectors**

www.allconnectors.de  
 Tel.: 0049 711 7009503  
 70754 Filberstadt - Germany

info@allconnectors.de  
 Fax: 0049 711 7009504  
 Kettnerstr. 25

PART NO. DBX2-ES-1515		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIP TION:	AREA	REVISIONS	HK	DATE
DWG NO. DBX2-ES-1515								
FILE NO.		DRAWING BY						
UNIT / mm	SCALE 1:1	PROJECTION						