



T:1.6 Dimensions of PC board holes  
Tolerance :  $\pm 0.05$ (Printed-top view)

4	HOUSING	1	PBT4815	UL-94V0(BLACK)
3	TERMINAL	1	C2680 t=0.50	Ag PLATED
2	TERMINAL	1	C5191 t=0.25	Ag PLATED
1	TERMINAL	1	C5191 t=0.50	Ag PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL:  $\pm 0.3$

**RoHS Compliant**

**All Connectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70794 Filderstadt - Germany

info@allconnectors.de  
Fax: 0049 711 7009504  
Kettnerstr. 25

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT / mm SCALE 1 : 1  
DATE  
SIZE A4

TOLERANCES ARE

X  $\pm$   
X  $\pm$   
.XX  $\pm$   
.XXX  $\pm$   
ANG  $\pm$

P PROJECTION



**ORDER INFORMATION**

DCJ-R3010-145-LF  
SERIES | LEADFREE  
1.45Ø  
WIDTH 10.0mm  
POST 3.0mm  
DIP 90°

DESCRIPTION: DC POWER JACK