



T:1.6 Dimensions of PC board holes
Tolerance : ± 0.1 (Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-DPE13-20	$\phi 2.0$	1
DCJ-DPE13-25	$\phi 2.5$	3
		2

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ± 0.3

DCJ-DPE13-xx-LF
LEADFREE
20:2.0 DIA.
25:2.5 DIA.
RoHS Compliant

LTR	PART NAME	QTY	MATERIAL	REMARK
6	COVER	1	PBT 4815	UL-94V0(BLACK)
5	AXIS SUPPORT	1	C2680	MB:Cu Sn PLATED
4	PIN	1	C2680	MB:Cu Ni PLATED
3	SPRING	1	C5191	MB:Cu Sn PLATED
2	FLAT PIECE	1	C2680	MB:Cu Sn PLATED
1	HOUSING	1	PBT 4815	UL-94V0(BLACK)

Allconnectors

www.allconnectors.de
Tel.: 0049 711 7009503
76794 Filzbergstraße - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kallertstraße, 25

PART NO. DCJ-DPE13-xx

DWG NO. DCJ-DPE13-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX \pm
AWG

DESCRIPTION:

DC POWER JACK

AREA

REVISIONS

HK

DATE