

T:1.6 Dimensions of PC board holes
Tolerance : ±0.1(Printed-top view)

CAT. NO.	PIN	SCHEMATIC
DCJ-RKPN-20	φ2.0	
DCJ-RKPN-25	φ2.5	
DCJ-RKPN-30	φ3.0	

UNLESS OTHERWISE SPECIFIED, TOLERANCE ON DECIMAL: ±0.3

6	HOUSING	1	PBT 4815	UL-94V0(BLACK)
5	COVER	1	PBT 4815	UL-94V0(BLACK)
4	PIN	1	C2680	MB:Cu Cu/Sn PLATED
3	SHUNT TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED
2	TIP SPRING	1	C5191 t=0.25	MB:Cu Cu/Sn PLATED
1	CENTER PIN TERMINAL	1	C2680 t=0.5	MB:Cu Cu/Sn PLATED
LTR	PART NAME	QTY	MATERIAL	REMARK

RoHS Compliant

All Connectors


www.allconnectors.de
Tel.: 0049 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0049 711 7009504
Kettnerstr. 25

DRAWING BY CY		TOLERANCES ARE X. ± .X ± .XX ± .XXX ± ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PJECTION	



ORDER INFORMATION



DESCRIPTION: DC POWER JACK