



**NOTES:**  
**1. DIELECTRIC STRENGTH:**  
 AC 500 V at 1 MIN.  
**2. INSURATION RESISTANCE:**  
 DC 500 V/100 MA MIN.

|    |              |
|----|--------------|
| 5  | PVC BLACK    |
| 4  | BRASS NICKEL |
| 3  | BRASS NICKEL |
| 2  | BRASS NICKEL |
| 1  | POM BLACK    |
| NO | CONTENT      |

RoHS Compliant

TOLERANCES ARE

**All Connectors**

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X ±  
 X ±  
 .XX ±  
 .XXX ±  
 ANG ±



ORDER INFORMATION

DCP-A-5521D8-LF  
 SERIES | LEADFREE  
 CONTACT 8.5mm  
 ID: 2.1Ø  
 OD: 5.5Ø  
 ASSEMBLY

DESCRIPTION: **DC PLUG 5.5\*2.1\*9.5L AEESEMBLY TYPE**

www.allconnectors.de  
 Tel.: 0049 711 7009503  
 70791 Filderstadt - Germany

info@allconnectors.de  
 Fax: 0049 711 7009504  
 Kettnerstr. 25