



1. Dielectric strength: AC 500V/1 minute.
2. Insulation resistance: 100MΩ Min. (at 500V DC)
3. Contact resistance: 30mΩ Max.

4. Rating: 18V, 2A.

項目	圖面號碼	零件名稱	材料	處理	數量
△ 7	190-067	外殼	ABS		1
6	170-184	彈片 B	黃銅	鍍鎳	1
5	170-185	彈片 A	黃銅	鍍鎳	1
△ 4	176-003	墊片	PBT(HB)		1
3	119-106	鎖牙套管	黃銅	鍍鎳	1
2	119-105	螺帽	黃銅	鍍鎳	1
1	150-217	5.5X2.1DC 插頭		鍍鎳	1

RoHS Compliant

All Connectors

www.allconnectors.de
 info@allconnectors.de
 Tel.: 0049 711 7009503
 40799 Hilderstadt - Germany

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4

TOLERANCES ARE
 X ±
 X ±
 .XX ±
 .XXX ±
 ANG ±



ORDER INFORMATION

DCP-AS-5521S-LF
 SERIES | LEADFREE
 | SHORT
 | ID: 2.1Ø
 | OD: 5.5Ø
 SCREW ASSEMBLY

DESCRIPTION: 5.5X2.1DC 插頭 (內鎖牙裝配) 9.5mm