



DASM-JA-05-LF
LEADFREE
RoHS Compliant

A-A SECTION

6	Contact Terminals	Brass	Silver Ptd.	5
5	5P180 Housing	ABS		1
4	Strain Boot	PVC		1
3	Setscrew	Steel	Nickel Ptd.	1
2	"T" Cable Holder	Steel	Nickel Ptd.	1
1	Shell Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

Specifications

rating :

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

Allconnectors

www.allconnectors.de
info@allconnectors.de
ZUSCHNEIDERSTR. 25
70529 HILDESHAIM - GERMANY

info@allconnectors.de
Fax: 0049 7141 909090
Kette 11/18/2018

PART NO. DASM-JA-05

DWG NO. DASM-JA-05

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2

.XX ± 0.1

.XXX ±

AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE