



DAMS-JA-06-LF
LEADFREE
RoHS Compliant

No.	Description	Material	Treat	Q'ty
1	Housing Holder dn	Zn Alloy	Nickel Ptd.	1
2	Housing Holder up	Zn Alloy	Nickel Ptd.	1
3	Screw Cap	Brass	Nickel Ptd.	1
4	Strain Relief	TPR		1
5	Shell	PA6		1
6	Cable Holder	Steel	Nickel Ptd.	1
7	Screw	Steel	Nickel Ptd.	2
8	Housing	PA66		1
9	Terminals	Brass	Gold Ptd.	6

Specifications
rating :

250V AC 5A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

Protection Degree : IP40

Cable Outlet : 3~6mm/6~8mm

All connectors

www.allconnectors.de
Tel.: 0019 711 7009503
70794 Filderstadt - Germany

info@allconnectors.de
Fax: 0019 711 7009501
Kettenstr. 25

PART NO. DAMS-JA-06

DWG NO. DAMS-JA-06

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ±
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE