



|            |                    |                 |              |             |
|------------|--------------------|-----------------|--------------|-------------|
| <b>5</b>   | TERMINALS          | Brass           | Silver Ptd.  | 3           |
| <b>4</b>   | 3P HOUSING         | PA66            |              | 1           |
| <b>3</b>   | SCREW NUT          | Brass           | Nickel Ptd.  | 1           |
| <b>2</b>   | NEGATIVE CONTACT   | Copper          | Nickel Ptd.  | 1           |
| <b>1</b>   | COVER              | Zn Alloy        | Nickel Ptd.  | 1           |
| <b>No.</b> | <b>Description</b> | <b>Material</b> | <b>Treat</b> | <b>Q'ty</b> |

### Specifications

rating : **100V AC 4A MAX**  
 contact resistance :  
 pins-30mΩ MAX; shell-50mΩ MAX  
 insulation resistance :  
 MIN 100 MEGΩ @500V DC  
 voltage withstand :

DAMS-JS-03-LF  
 LEADFREE  
 RoHS Compliant

250V AC R.M.S. for 1 minute



|                     |           |               |  |   |   |    |      |
|---------------------|-----------|---------------|--|---|---|----|------|
| PART NO. DAMS-JS-03 |           | CHECKED BY CY |  | TOLERANCES ARE<br>.X±<br>.XX±<br>.XXX±<br>AWG | DESCRIPTION: <b>DIN 3P SCREW LOCKING<br/>SOCKET PANEL MOUNT</b> |    |      |
| DWG NO. DAMS-JS-03  |           | DRAWING BY    |  |   |   |    |      |
| FILE NO.            |           | PROJECTION    |  | AREA  | REVISIONS   | HK | DATE |
| UNIT / mm           | SCALE 1:1 |               |  |   |   |    |      |