

DASM-JA-05-LF  
LEADFREE  
RoHS Compliant

A-A SECTION

6	Contact Terminals	Brass	Silver Ptd.	5
5	5P180 Housing	ABS		1
4	Strain Boot	PVC		1
3	Setscrew	Steel	Nickel Ptd.	1
2	"T" Cable Holder	Steel	Nickel Ptd.	1
1	Shell Cover	Zn Alloy	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

**Specifications**

rating :

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

**Allconnectors**

www.allconnectors.de  
Tel.: 0049 711 7935103  
70754 Tilderstadt - Germany

Info@allconnectors.de  
Fax: 0049 711 7069504  
Kettnerstr. 25

PART NO. DASM-JA-05

DWG NO. DASM-JA-05

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ± 0.1  
.XXX ±  
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE