

**SPECIFICATIONS:**

1. CONTACT RESISTANCE : 20m OHM MAX
2. INSULATION RESISTANCE : 100M OHM AT 500V D.C.
3. VOLTAGE WITHSTANDING : AC 500V 1 MINUTE .
4. INSERTION FORCE : 5.0KG MAX
5. WITHDRAWAL FORCE : 1-3.5 KG
6. LIFE TEST : 5,000 CYCLES MIN. AFTER TESTING, CONTACT RESISTANCE SHALL NOT EXCEED 100m OHM .

未指定尺寸公差為±0.2mm

4.	CONTACT TERMINAL	3	BSR-H/2 0.7t	TIN	
3.	PLATE	1	BAKELITE	PL-PEM 1.4t	
2.	EARTH TERMINAL	1	PBSR-H 0.2t	NICKEL PLATED	
1.	BODY	1	P.B.T.		UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

**All Connectors**

www.allconnectors.de  
Tel.: 0049 711 7009503  
70794 Filderstadt - Germany

info@allconnectors.de  
Fax: 0049 711 7009504  
Kettnerstr. 25


**RoHS Compliant**

DRAWING BY CY  
CHECKED BY GENIUS  
UNIT/mm SCALE 1:1  
DATE  
SIZE A4

TOLERANCES ARE

X ±  
X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION



ORDER INFORMATION

DJ-M5-0503-LF  
SERIES | 5P3C | LEADFREE  
5.0mm  
METAL

DESCRIPTION: