



SPECIFICATIONS:

1. CONTACT RESISTANCE : 20m OHM.
2. INSULATION RESISTANCE : DC 500V 100M OHM MIN.
3. VOLTAGE WITHSTANDING : AC 500V 1 MINUTE.
4. INSERTION FORCE : 4KG MAX.
5. WITHDRAWAL FORCE : 1 - 3.5 KG.
6. LIFE TEST : 5,000 CYCLES MIN. AFTER TESTING , CONTACT RESISTANCE SHALL NOT EXCEED 100m OHM.
7. CURRENT RATING : AC : 100V 2A.
DC : 24V 1A.

DJ-SQ-05-LF
LEADFREE
RoHS Compliant

4.	EARTH TERMINAL	1	PBSR 0.25t	TIN	
3.	CONTACT TERMINAL	8	BSR-H/2 0.7t	TIN	
2.	COVER	1	P.B.T.		UL94V-0
1.	BODY	1	P.B.T.		UL94V-0
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

All Connectors

www.allconnectors.com
TEL: 0048 222 7008300
NIPON Road, Gdansk, Poland

PART NO. DJ-SQ-05

DWG NO. DJ-SQ-05

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

X ± 0.2
XX ± 0.1
XXX ±
AWG

DESCRIPTION:			
AREA	REVISIONS	HK	DATE