



DAMS-PA-05-LF
LEADFREE
RoHS Compliant

A-A SECTION

8	Contact Terminals	Brass	Silver Ptd.	5
7	5P180 Housing	ABS		1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Setscrew	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strain Boot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

**Specifications
rating :**

100V AC 1A MAX

contact resistance :

pins-30mΩ MAX; shell-50mΩ MAX

insulation resistance :

MIN 100 MEGΩ @500V DC

voltage withstand :

250V AC R.M.S. for 1 minute

Allconnectors

www.allconnectors.de
Tel.: 0049 /11 /005049
70794 Fildefeld, Germany

info@allconnectors.de
Fax: 0049 /11 /0095041
Kollektormstr. 25

PART NO. DAMS-PA-05

DWG NO. DAMS-PA-05

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE