

A-A SECTION



8	Contact Terminals	Brass	Silver Ptd.	5
7	5P240 Housing	ABS		1
6	Spring Ring	Steel	Nickel Ptd.	1
5	Setscrew	Steel	Nickel Ptd.	1
4	"T" Holder	Steel	Nickel Ptd.	1
3	Strain Boot	PVC		1
2	Screw Cap	Brass	Nickel Ptd.	1
1	Shell Cover	Brass	Nickel Ptd.	1
No.	Description	Material	Treat	Q'ty

Specifications
rating :

100V AC 1A MAX
 contact resistance :
 pins-30mΩ MAX; shell-50mΩ MAX
 insulation resistance :
 MIN 100 MEGΩ @500V DC
 voltage withstand :
 250V AC R.M.S. for 1 minute

Allconnectors

www.allconnectors.de info@allconnectors.de
 Tel: 0049 711 2009415 Fax: 0049 711 2009415
 70794 Filzbergstr. 25 Krefeld, Germany

PART NO. DAMS-PA-05B

DWG NO. DAMS-PA-05B

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
 .XX ±
 .XXX ±
 AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE