



**MATERIALS**

- 1. HOUSING : PBT+25%
- 2. TERMINAL : BRASS, GOLD/TIN PLATED
- 3. FRONT SHIELD : SPCC, NICKEL PLATED
- 4. BACK SHIELD : SPCC, TIN PLATED

**SPECIFICATION:**

- 1. CURRENT RATING: 1.5AMP. MAX
- 2. DIELECTRIC WITHSTANDING VOLTAGE: AC 500Vmin R.M.S.
- 3. INSULATION RESISTANCE: 1000MV MIN. AT 500V DC
- 4. CONTACT RESISTANCE: 20mV MAX
- 5. OPERATING TEMPERATURE: 0°C TO +85°C
- 6. MAX. PROCESSING TEMPERATURE: 230°C FOR 30~60 SECONDS (HI.-TEMP. PLASTIC)

PART NO.	PLATING	COLOR
DVI-PS-24+1	GOLD(3u') OR TIN PLATED	WHITE

**NOTE:**

THE 14PIN HEGHEST SHORT 0.76m/m OTHER PIN

**Allconnectors**

www.allconnectors.de  
T-L: 0049 711 2094503  
79794 Hildersriedl Germany

Info@allconnectors.de  
Fax: 0049 711 2094504  
Kottlerstr. 2b

PART NO. DVI-PS-24+1

DWG NO. DVI-PS-24+1

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2

.XX ± 0.1

.XXX ±

AWG

DESCRIPTION: DVI 24+1 公半金白膠

AREA

REVISIONS

HK

DATE