


REV.	ECN NO.	ADDP.
I	DC-14012	Joseph Chou 8/1/2014

FEATURE:
INSULATOR
 Glass-Filled P.B.T. is 94V-0 rated
CONTACT
 Phosphor Bronze selective gold plating
 over nickel

SPECIFICATION:
 Current Rating : 3 amperes
 Contact Resistance : 20 miniohms max.
 Operation Temperature : -55°c to +105°c
 Voltage Rating : 800 VAC 1 minute
 Insulation Resistance : 5000 megaohms min.
 Insertion Force : 412 grams max. per pair
 Withdrawal Force : 32 grams min. per pair

NOTE:
ORDERING INFORMATION
 BX
 SERIES NO. CONTACTS NO. TAIL LENGTH. ROW TO ROW DIN.



Allconnectors
 www.allconnectors.de info@allconnectors.de
 Tel.: 0049 711 7009503 Fax: 0049 711 7009504
 70794 Filderstadt - Germany Kettmerstr. 25

TAIL LENGTH	L	ROW TO ROW	S
A	3.10	A	5.08
B	3.51	B	3.96

X ₂ 1.10	X ₂ 0.38	XX ₂ 1.25	NAME (INTENDED USE)
X ₂ °	X ₂ °	XX ₂ °	EDGE CARD CONN.
UNITS mm	DATE: 8/1/2014	PART NO. (INTENDED USE)	TITLE:
MATL:	CONTACT:	4201 SERIES	EDGE CONNECTOR 3.96mm PITCH
	PHOSPHOR BRONZE	APPR: Joseph Chou	WITH MD-HIGH R/A MOUNTING EARS
	HOUSING:	CHKD: Ching-Yi Yu	R/A TYPE
	P.B.T. UL94V-0	DR: Zi.Hsiang.Chen	DRW NO. 011-0110-542
			SCALE SHEET REV
			N/A 1/1 I

CONTACTS NO.	DIM A	DIM B	DIM C	DIM D	DIM E
18/36	93.02	86.62	79.02	75.72	67.32
20/40	100.94	94.54	86.94	83.64	75.24
22/44	108.86	102.46	94.86	91.56	83.16
28/56	132.62	126.22	118.62	115.32	106.92
30/60	140.54	134.14	126.54	123.24	114.84

