



▼ CE PITCH 2.54MM I.D.C. CARD EDGE CONNECTOR
FOR PITCH 1.27MM CENTER FLAT RIBBON CABLE

- MATERIAL & FINISH**
 *INSULATOR: PBT+GLASS FIBER UL 94V-0
 *CONTACT: BRASS
 *FINISH: GOLD-PLATED OVER NICKEL
- SPECIFICATIONS**
 *CURRENT RATING: 1A AC,DC
 *VOLTAGE RATING: 250V AC,DC
 *TEMPERATURE RANGE: -44°C TO +105°C
 *CONTACT RESISTANCE: 20MΩ MAX
 *INSULATION RESISTANCE: 1,000MΩ MIN
 *WITHSTANDING VOLTAGE: 500V AC/MIN

E-C2-xx-LF
LEADFREE

RoHS Compliant

PART NO	DIM A	DIM B	PART NO	DIM A	DIM B	PART NO	DIM A	DIM B
E-C2-10	10.16	22.03	E-C2-26	30.48	42.40	E-C2-50	60.96	72.90
E-C2-14	15.24	27.10	E-C2-34	40.64	52.60	E-C2-56	68.58	80.54
E-C2-16	17.78	29.60	E-C2-40	48.26	60.22	E-C2-60	73.66	85.43
E-C2-20	22.86	34.80	E-C2-44	53.34	65.30	E-C2-64	78.74	90.51

DIMENSIONS:MM

 www.allconnectors.de info@allconnectors.de Tel.: 0049 711 7009503 Fax: 0049 711 7009504 70791 Filderstadt - Germany Kettnerstr. 25	PART NO. E-C2-xx		APPROVED BY CY		TOLERANCES ARE		DESCRIPTION:			
	DWG NO. E-C2-xx		DRAWING BY		X XX XXX AWG					
	FILE NO.		PROJECTION				AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1								