

FEATURE:
 INSULATOR
 Glass-Filled P.B.T. is 94V-0 rated
 CONTACT
 Phosphor Bronze selective gold plating
 over nickel

SPECIFICATION:
 Current Rating: 3 amperes
 Contact Resistance: 20 miniohms max.
 Operation Temperature: -55°C to 105°C
 Voltage Rating: 800 VAC 1 minute
 Insulation Resistance: 5000 megaohms min
 Insertion Force: 412 grams max. per pair
 Withdrawal Force: 32 grams min. per pair

CONTACTS	DIM A	DIM B	DIM C	DIM D	DIM E
NO 12/24	51.69	45.09	37.38	33.22	27.94
22/44	77.09	70.49	62.78	58.62	53.34
24/48	82.17	75.57	67.86	63.70	58.42
25/50	84.71	78.11	70.40	66.24	60.96
28/56	92.33	85.73	78.02	73.86	68.58
30/60	97.41	90.81	83.10	78.94	73.66
35/70	110.11	103.51	95.80	91.64	86.36
36/72	112.65	106.05	98.34	94.18	88.90
43/86	130.43	123.83	116.12	111.96	106.68
44/88	133.17	126.57	118.66	114.50	109.22
50/100	148.21	141.61	133.90	129.74	124.46

RoHS Compliant

All Connectors

www.allconnectors.de info@allconnectors.de
 Tel.: 0049 711 7009503 Fax: 0049 711 7009504
 70794 Filderstadt - Germany Kettnerstr. 25

TOLERANCES ARE


X ±
 X ± 0.38
 XX ± 0.25
 XXX ±
 ANG ±

DRAWING BY CY
 CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4 PROJECTION



ORDER INFORMATION

E-DME-xxx-LF

SERIES MIDDLE EARS LEADFREE

006~072WAY

DIP 180°

DESCRIPTION: 2.54mm EDGE CARD SCCONNECTORS