



MATERIAL

INSULATOR: HI-TEMP PPS UL 94V-0, 240°C
 CONTACT: COPPER ALLOY.
 PLATING: MATING AREA - GOLD FLASH GOLD OVER NICKEL.
 SOLDER AREA - TIN OVER NICKEL.

ELECTRICAL

VOLTAGE RATING: 250 VAC RMS.
 CURRENT RATING: 1 AMP.
 DIELECTRIC WITHSTANDING VOLTAGE: 500 VAC RMS 60Hz FOR 1 MINUTE.
 INSULATION RESISTANCE: 1000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 30 MILLIOHMS MAX.

MECHANICAL

RETENTION FORCE: 460 GRAMS MIN PER CONTACT.
 INSERTION FORCE: 230 GRAMS MAX PER CONTACT PAIR.
 WITHDRAWAL FORCE: 15 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL

TEMPERATURE RANGE: -55°C TO +85°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
D4	8.64	3.81	1.27	38	30.23	25.40	22.86
D6	9.91	5.08	2.54	40	31.50	26.67	24.13
D8	11.18	6.35	3.81	42	32.77	27.94	25.40
10	12.45	7.62	5.08	44	34.04	29.21	26.67
12	13.72	8.89	6.35	46	35.31	30.48	27.94
14	14.99	10.16	7.62	48	36.58	31.75	29.21
16	16.26	11.43	8.89	50	37.85	33.02	30.48
18	17.53	12.70	10.16	52	39.12	34.29	31.75
20	18.80	13.97	11.43	54	40.39	35.56	33.02
22	20.07	15.24	12.70	56	41.66	36.83	34.29
24	21.34	16.51	13.97	58	42.93	38.10	35.56
26	22.61	17.78	15.24	60	44.20	39.37	36.83
28	23.88	19.05	16.51	80	56.90	52.07	49.53
30	25.15	20.32	17.78	100	69.60	64.77	62.23
32	26.42	21.59	19.05	120	82.30	77.47	74.93
34	27.69	22.86	20.32	182	121.67	116.84	114.30
36	28.96	24.13	21.59				

RoHS Compliant

www.allconnectors.de
 Tel: 0349 711 7004508
 70724 Filderstadt - Germany

info@allconnectors.de
 Fax: 0349 711 7004674
 Kettenerstr. 25

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT/mm SCALE 1:1
 DATE

TOLERANCES ARE
 X ± 0.30
 X ± 0.30
 XX ± 0.20
 XXX ± 0.20
 ANG ± 0.20

SIZE A4 PROJECTION



ORDER INFORMATION

HE-VP-xxx-LF

SERIES | 180°SMT | LEADFREE | 004-182WAY | WITH LOCATING PEG

DESCRIPTION: 1.27 PITCH CARD EDGE SMT